

Technical Data Sheet

CE-3030 (Construction Chemicals)

Product Description

- Chemical Constitution: Modified cellulose ether for gypsum plaster
- Physical Form: White to slightly yellow powder
- Delayed Solubility: no

Product Specification

- Viscosity: approximately. 45000 mPa•s*
- Moisture content: ≤8.0%
- Residue on ignition: ≤6.0%
- Particle Size: above 95% through 80 mesh
- Bulk density: 300 -500 g/l

*Note: The test conditions for the viscosity of 2% aqueous solution, Brookfield viscometer, 20rpm., 20 ℃.

Application and Properties

- Good Workability
- Good Water Retention
- Good Adhesion
- Good Operable time

Packaging and Storage

- CE-3030 is supplied in multi-ply paper bags with polyethylene intermediate layer, containing 25 kgs.
- CE-3030 has a long shelf life (2 years) stored in dry, normal temperature condition and no direct sun shine.

This product specification information is based on our present state of knowledge and to provide general notes on our products and application. It should therefore not be construed as guaranteeing specific properties of the products or their suitability for specific application. Recommendation is made to check suitability of our product by doing tests on your own.

If you need further information, please contact us or home: <http://www.yinduntech.com.cn>

Shaanxi Yindun Building Technology Co., Ltd.

Address: No. 109, Xingfu South Road, Xi'an City, Shaanxi Province, China

Tel: 400-003-1109 E-mail: yinduntech@126.com